



30 - 400 kVA

DSP POWER H SERIES

UNINTERRUPTIBLE POWER SUPPLIES

3 LEVEL TECHNOLOGY IGBT RECTIFIER DSP CONTROL

The new DS Power range UPS uses the latest DSP technology to be programmed to suit a wide variety of electrical environments without impeding its performance. With the DS Power range, efficiency, reliability and functionality are enhanced to levels unattainable with the old analogue technology. This technology does not only create significant increase in MTBF, but the capability of DSP to accurately manipulate signals at very high speed permits all the UPS subsystems to be controlled with greatly increased precision.

GENERAL SPECIFICATIONS

- Transformerless UPS topology
- 3 Level topology
- High input power factor
- High efficiency up to 95%
- Cold start function
- Static and maintenance by-pass switch
- Output short circuit and overload protection
- External REPO switch input
- 512 events memory (512 events 45000 alarms)
- Clock and calender (battery supported)
- Automatic battery test, remaining battery time indicator
- Temperature compensated charge system (optional)
- 2 RS232 serial ports and 12 dry contact outputs
- 3 DSP controlled modular structure
- Optional SNMP and MODBUS adaptors
- Optional graphical panel
- Optional usb flash memory
- Full digital structure
- Small footprint
- Ecomode operation (optional)
- Fewer electronic components
- Output current limiting
- Advanced diagnostics for the input
- Selectable input/output voltage/frequency/range
- Split by-pass input (second input)
- Output DC leakage protection
- Separate DSP for inverter control
- Separate DSP for the PFC
- 3 level battery protection
- High charge current capacity
- Charge/discharge current indicator
- Advanced remote control
- Manufactured according to EC Directive; EN62040
- 5 years spare parts support
- 2 years warranty



CE

3 phase in / 3 phase out



30 - 400 kVA

TECHNICAL SPECIFICATIONS

MODEL	DS330H	DS340H	DS360H	DS380H	DS3100H	DS3120H	DS3160H	DS3200H	DS3250H	DS3300H	DS3400H
Power (kVA)	30	40	60	80	100	120	160	200	250	300	400
INPUT											
Voltage	380/400 VAC 3P + N + G ± 20% (at 100% load) / - 40% (at 70% load)										
Frequency	50Hz / 60Hz, ± 5%										
Power factor	≥ 0.99 (at 100% load)										
(THDI) (*)	≤ 3%										
By-pass voltage	380/400 VAC 3 Phase + N, ± 10%										
Voltage distortion	≤ 10%										
Protection	Fuses, Voltage & Frequency tolerance, Input power limit, Phase sequency indicator										
OUTPUT											
Power (kW)	27	36	54	72	90	108	144	180	225	270	360
Power factor	0,9 (0,8 and 1 optional)										
Voltage	380/400 VAC 3P + N, ± 1% (415 VAC optional)										
Frequency	50Hz / 60Hz										
Frequency tolerance	Line synchronized: ± 2% (adjustable) / Free running: ± 0,1%										
Efficiency	up to 95%										
Crest factor	3:1										
Overload protection	100% - 125% load: 10 min, 125% - 150% load: 1 min, - > 150% load: by pass										
Other protections	Advanced short circuit, Voltage tolerance, DC balance, Regenerative load, Current limiting										
Voltage THD	≤ 3% (at 100% linear load)										
BATTERIES											
Type	VRLA AGM / GEL / NiCd										
Number of batteries	2x30 (±30): 60 pieces										
Charge voltage	2x405 VDC										
End of discharge voltage	2x300 VDC										
Battery cabinet	Internal					External					
Battery ambient temperature	25°C										
Protections	3 level alarms, Battery fuses, Charging current limit, Temperature compensation (optional)										
Automatic testing	Standard every 72 hours (adjustable)										
GENERAL											
Standards	EN62040-1, EN62040-2, EN62040-3										
User interface	4 lines LCD panel, Mimic leds, 5 vector buttons, Buzzer, Optional TFT panel										
Indicators	P-N voltage, P-P voltage, Current, Power, Crest Factor, Frequency, PF, Service Time										
Advanced	Self diagnostics, 3 maintenance time indicators, Calibration over RS232, operating hour meter										
Communication	2xRS232 serial ports, 4 standard and 8 optional DRY contact alarm relays										
Inputs	EPO input, Interactive battery panel input, Genset input										
Genset kit	Standard (programmable)										
Software	Standard T-Mon UPS Management Software (3 clients + 1 server management)										
Alarm logging	Standard:with time & date 512 events										
Protections	Power module over-temperature, Overcurrent, Temperature high alarm										
Temperature range	0°C - 40°C										
Protection degree	IP20										
Relative humidity	95% max. (non-condensing)										
Altitude	< 1000m above sea level										
Acoustic noise	< 57dBA	< 62dBA			< 65 dBA			< 68dBA			
Weight without batteries (kg)	100	173	197	209	220	232	265	470	525	635	680
Dimensions (mm) HxWxD	1040x400x815		1440x515x855					1900x880x775		1900x1250x775	
OPTIONS											
Different input / output voltage	Please ask										
Transformer	Galvanic isolation transformer at the input & output (internal)										
Software	T-Mon Admin Multi UPS monitoring 10-50-100-200 clients, T-Mon Server 50-100-200 clients										
Adaptors	SNMP, RS485, Remote monitoring panel, MODBUS (RS485 or TCP/IP), USB Alarm Logger, TCP/IP, GSM/GPRS Modem, Comport multiplexer										
Parallel operation	Up to 8 units										